





## ProGrip10 InfraRed Remote Control

	<p>System Part Number: <b>UBIR-PG10-10</b></p> <p>InfraRed Remote Control System consisting of ProGrip10 IR Transmitter &amp; DC10 IR Receiver Unit with N/O Momentary Relay Outputs.</p> <p>AC Transmitter Charger included.</p>
---	---

Standard System Package: (Customised label options available for ProGrip Transmitter to include button functions and company logo. Protective Bumper can also be supplied in Yellow, Green or Grey)

**1 x UBIR-PG10-10 includes:**

<p><b>UB/PRO10/IR/TX</b></p> 	<p><b>UB/RX/DC10/IR01</b></p> 	<p><b>PA31/CHARGER/01</b></p> 
---	---	--

**Part Numbers:**

<b><u>UBIR-PG10-10</u></b>	<b>ProGrip10 IR Remote Control System</b>	
<b><u>UB/PRO10/IR/TX</u></b>	<b>ProGrip10 IR Transmitter</b>	
<b><u>PA31/CHARGER/01</u></b>	<b>AC Transmitter Charger (DC optional)</b>	
<b><u>UB/RX/DC10/IR01</u></b>	<b>DC10 IR Receiver Unit</b>	

**Optional Accessories:**

<b><u>PA31/CHARGER/02</u></b>	<b>DC Transmitter Charger</b>	
<b><u>PA08/BOP/005</u></b>	<b>Lanyard Loop &amp; Lanyard for ProGrip</b>	
<b><u>PA08/BOP/006</u></b>	<b>Universal Belt-Clip for ProGrip</b>	
<b><u>PA08/BOP/013</u></b>	<b>Wall Holder for ProGrip</b>	

## Technical Specifications

### ProGrip10 IR Transmitter

Number of buttons:	10
Battery type:	3 x AA (Rechargeable LiPo)
Dimensions:	159.4 x 77.9 x 35.5mm
Weight:	240g
IP Protection rating:	IP65
Operating temperature:	-20 °C to +55 °C
Transport/storage temperature:	-40 °C to +70 °C
Antenna:	N/A
Operating distance range:	Up to 30 metres line-of-sight
Operating InfraRed frequency band:	36KHz PWM InfraRed

### DC10 IR Receiver Unit

Power supply:	12-24 VDC
Outputs:	10
Max voltage to contacts:	12A @ 250VAC & 24VDC
Dimensions:	201.0 x 122.4 x 55.0mm
IP protection rating:	IP65
Operating temperature:	-20 °C to +55 °C
Transport/storage temperature:	-40 °C to +70 °C
Antenna:	N/A
Operating InfraRed frequency band:	36KHz PWM InfraRed

